

Serial Output Wind Sensor



Model 09101
Wind Monitor-SE

The Wind Monitor-SE combines the performance and durability of our standard Wind Monitor with a unique optical encoder wind direction transducer and serial output signal.

The Wind Monitor-SE offers maximum versatility in a conventional wind sensor. An optical encoder is utilized for vane angle measurement, thereby eliminating the characteristic deadband and wear of potentiometer transducers. The serial output signal is ideal for interfacing with modern data acquisition systems.

The wind speed sensor is a four blade helicoid propeller that turns a multi-pole magnet. Propeller rotation induces a variable frequency signal in a stationary coil, eliminating the need for slip rings and brushes.

The wind direction sensor is a durable molded vane. Vane angle is detected by a custom optical encoder. The encoder is an absolute type so direction output remains accurate even if power is interrupted.

Wind speed and wind direction signals are converted to a serial output by the on-board microprocessor circuit. The serial signal is fully addressable for up to 16 separate sensors. Conventional voltage outputs may also be selected simply by moving an internal jumper.

The Wind Monitor-SE is designed for superior environmental resistance. Housing parts are UV stabilized thermoplastic. Fittings are stainless steel and anodized aluminum. Precision grade stainless steel ball bearings are used throughout.

The instrument mounts on standard 1 inch pipe.



Specifications

Range:

Wind speed: 0-60 m/s (134 mph)
Gust survival: 100 m/s (220 mph)
Wind direction: 0-360 degrees

Resolution:

Wind speed: 0.1 unit (m/s, kts, mph, km/h)
Wind direction: 1 degree

Accuracy:

Wind speed: ± 0.3 m/s (0.6 mph)
Wind direction: ± 2 degrees

Dynamic Response:

Damping ratio: 0.3
Damped natural wavelength: 7.4 m (24.3 ft)
Undamped natural wavelength: 7.2 m (23.6 ft)

Threshold:*

Propeller: 1.0 m/s (2.2 mph)
Vane: 1.1 m/s (2.5 mph) @ 10° displacement

Available Outputs:

Voltage Output:
WS: 0-5 VDC for 0-100 m/s
WD: 0-5 VDC for 0-540°
Serial RS-485:
RMY, NCAR, or NMEA protocols
Polled or continuous output

Power Requirement:

11-24 VDC, 20 mA

Dimensions:

Overall height: 37 cm (14.6 in)
Overall length: 55 cm (21.6 in)
Propeller: 18 cm (7.0 in) diameter
Mounting: 34 mm (1.34 in) diameter (standard 1 inch pipe)

Weight:

Sensor weight: 1.0 kg (2.2 lbs)
Shipping weight: 2.3 kg (5 lbs)

Operating Temperature:

-50 to 50° C

**Nominal values, determined in accordance with ASTM standard procedures.*

Ordering Information

MODEL

WIND MONITOR-SE09101

CE Complies with applicable CE directives.
Specifications subject to change without notice.



R.M. YOUNG COMPANY
2801 Aero-Park Drive
Traverse City, Michigan 49686 U.S.A.
TEL: (616) 946-3980 FAX: (616) 946-4772
E-mail: met.sales@youngusa.com
Web Site: www.youngusa.com